

SilCoat System Product use Guide

Refer to Application Guide SilCoat for more detailed application methods. This quick guide is to ensure you allow the correct materials and coverage rates when pricing.

Note that SilCoat is offered only as a repair and maintenance solution with a 5 year product warranty when a Building Consent is not required and a new membrane system with longer warranty is not an option for the client at this stage.

SilCoat Application for repairs and maintenance only	
Over Bitumen membranes	
1. VSC600 19 Lt Bleed Trap <i>Barrier required for Bitumen material</i>	Coverage approx. 2.0 - 2.5m ² / Lt (<i>Water-based clean up</i>) <i>not to be thinned</i> Coverage is dependent on smooth or chip surface. Dry time 12 - 24 hrs. Recoat would be required if no SilCoat topcoat is applied within 72hrs
2. VSC200 Epoxy Primer Kit Part A & B <i>Water-based clean up</i>	10m ² / Lt. <i>Can be thinned up to 20%.</i> <i>Allow to dry a minimum of 12-24 hours. Primer must be coated within 72 hours of the application.</i>
3. VSC300 / VSC310 / VSC320	Reinforcement of all laps, details, penetrations
4. Topcoats x 2 White or Grey	2.5m ² - 3m ² /Lt per coat <i>Minimum 4 hrs between coats. Turps or White spirits clean-up</i>
Product Warranty	5 Years
SilCoat Application for repairs and maintenance only	
Over <u>non</u>-bitumen membranes	
1. VSC200 Epoxy Primer Kit Part A & B <i>Water-based clean up</i>	10m ² / Lt. <i>Can be thinned up to 20%.</i> <i>Allow to dry a minimum of 12-24 hours. Primer must be coated within 72 hours of the application.</i>
2. VSC300 / VSC310 / VSC320 reinforcing	Reinforcement of all laps, details, penetrations
3. Topcoats x 2 White or Grey	2.5 - 3m ² /Lt per coat <i>Minimum 4 hrs between coats. Turps or White spirits clean-up</i>
Product Warranty	5 Years