

1. Identification of Substance & Company

Product

Product name	Epoxy Primer Kit Part B
Other names	GacoFlex E5320 Part B
Product code	VSC200
HSNO approval	HSR002679
Approval description	Surface Coatings and Colourants (Toxic [6.7]) Group Standard 2017
UN number	NA
DG class	NA
Proper Shipping Name	NA
Packaging group	NA
Hazchem code	NA
Uses	Part B of epoxy primer

Company Details

Company	Viking Roofspec	
Physical Address	80 Alexander Crescent	PO Box 14 451
	Otara	Panmure
	Auckland	Auckland 1741
	New Zealand	New Zealand
Telephone	0800 729 799	
Fax	0800 729 788	
Website	www.vikingroofspec.co.nz	

Emergency Telephone Number: 0800 764 766

2. Hazard Identification

Approval

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002679, Surface Coatings and Colourants (Toxic [6.7]) Group Standard 2017). The substance has been classified as hazardous according to the criteria in the Hazardous substances (Minimum Degrees of Hazard) Notice 2017.

Classes

Hazard Statements

6.3A	H315 - Causes skin irritation.
8.3A	H318 - Causes serious eye damage.
6.5B	H317 - May cause an allergic skin reaction.
6.7B	H341 - Suspected of causing cancer.
6.8B	H361 - Suspected of damaging fertility or the unborn child.
6.9B	H371 - May cause damage to organs through prolonged or repeated exposure.
9.1C	H412 - Harmful to aquatic life with long lasting effects.

SYMBOLS

DANGER



Other Classifications

There are no other classifications that are known to apply.

Precautionary Statements

- P101 - If medical advice is needed, have product container or label at hand.
- P102 - Keep out of reach of children.
- P103 - Read label before use.
- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P264 - Wash hands thoroughly after handling.
- P260 - Do not breathe vapours.
- P261 - Avoid breathing vapours.
- P270 - Do not eat, drink or smoke when using this product.
- P272 - Contaminated work clothing should not be allowed out of the workplace.
- P273 - Avoid release to the environment.
- P280 - Wear protective gloves/eye protection/face protection*.
- P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 - Immediately call a POISON CENTRE or doctor/physician.
- P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
- P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
- P363 - Wash contaminated clothing before reuse.
- P308+P313 - IF exposed or concerned: Get medical advice/ attention.
- P405 - Store locked up.

3. Composition / Information on Ingredients

Component	CAS/ Identification	Conc (%)
Limestone	1317-65-3	15-40%
Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines	68410-23-1	7-13%
Xylene	1330-20-7	1-5%
Bisphenol A epoxy resin	25068-38-6	1-5%
Ethylbenzene	100-41-4	1-5%
Triethylene tetramine (TETA)	112-24-3	0.1-1%

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

4. First Aid

General Information

If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel that you may have been harmed, burned or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service). IF exposed or concerned: Get medical advice/ attention.

Recommended first aid facilities Ready access to running water is required. Accessible eyewash is required.

Exposure

- Swallowed** Do NOT induce vomiting. Give a glass of water to drink. Contact a doctor.
- Eye contact** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE or doctor/physician.
- Skin contact** IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
- Inhaled** Generally, inhalation of vapours is unlikely to result in acute health effects. If coughing, dizziness or shortness of breath is experienced, remove the patient to fresh air immediately. If patient is unconscious, place in the recovery position (on the side) for transport and contact a doctor.

Advice to Doctor

Treat symptomatically

5. Firefighting Measures

Fire and explosion hazards:	There are no specific risks for fire/explosion for this chemical. It is non-flammable.
Suitable extinguishing substances:	Carbon dioxide, extinguishing powder or water jet. Fight larger fires with water jet or alcohol resistant foam.
Unsuitable extinguishing substances:	Unknown.
Products of combustion:	Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures.
Protective equipment:	Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat and eye protection.
Hazchem code:	NA

6. Accidental Release Measures

Containment	If greater than 1000L is stored, secondary containment and emergency plans to manage any potential spills must be in place. In all cases design storage to prevent discharge to storm water.
Emergency procedures	In the event of spillage alert the fire brigade to location and give brief description of hazard. Stop the source of the leak, if safe to do so. Shut off all possible sources of ignition. Wear protective equipment to prevent skin, eye and respiratory exposure. Clear area of any unprotected personnel. Contain using sand, earth or vermiculite. Do not use sawdust. Prevent by whatever means possible any spillage from entering drains, sewers, or water courses. (If this occurs contact your regional council immediately).
Clean-up method	Use absorbent (soil, sand or other inert material). Rags are not recommended for the clean-up of spills, as they may create fire or environmental hazard. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.
Disposal	Mop up and collect recoverable material into labelled containers for recycling or salvage. Recycle containers wherever possible. This material may be suitable for approved landfill. Dispose of only in accord with all regulations.
Precautions	Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation.

7. Storage & Handling

Storage	Avoid storage of harmful substances with food. Store out of reach of children. Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames. Avoid contact with incompatible substances as listed in Section 10.
Handling	Keep exposure to a minimum, and minimise the quantities kept in work areas. See section 8 with regard to personal protective equipment requirements. Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m³ for respirable particulates and 10mg/m³ for inhalable particulates when limits have not otherwise been established.

NZ Workplace Exposure Stds (2016)	Ingredient	WES-TWA*	WES-STEL
	limestone	10mg/m ³	data unavailable
	xylene	50ppm, 217mg/m ³	data unavailable
	ethylbenzene	100ppm, 434mg/m ³	125ppm, 543mg/m ³

* These workplace exposure standards are also Prescribed Exposure Standards (PES) under the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016.

Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

Personal Protective Equipment

Eyes



To protect eyes, it is recommended that goggles, safety glasses or full face mask be worn. Avoid wearing contact lenses.

Skin



Avoid repeated or prolonged skin contact. Wear overalls, rubber boots and impervious gloves, e.g. nitrile rubber, NBR gloves. Replace frequently. Gloves should be checked for tears or holes before use. Natural rubber, NR, Leather gloves are not suitable for this purpose.

Remove protective clothing and wash exposed areas with soap and water prior to eating, drinking or smoking. Wash hands after handling.

Respiratory

A respirator with an organic vapour cartridge when airborne concentrations approach the WES (section 8) should be used. If using a respirator, ensure that the cartridges are correct for the potential air contamination and are in good working order.

WES Additional Information

Not applicable

9. Physical & Chemical Properties

Appearance	viscous brown liquid
Odour	strong solvent odour
pH	no data
Vapour pressure	no data
Viscosity	no data
Boiling point	no data
Volatile materials	165g/L VOC
Freezing / melting point	no data
Solubility	high solubility in water
Specific gravity / density	1.29g/cm ³
Flash point	>93°C
Danger of explosion	no data
Auto-ignition temperature	no data
Upper & lower flammable limits	no data
Corrosiveness	corrosive to eyes

10. Stability & Reactivity

Stability	Stable
Conditions to be avoided	Containers should be kept closed in order to avoid contamination. Keep from extreme heat and open flames.
Incompatible groups	Oxidisers.
Substance Specific Incompatibility	none known
Hazardous decomposition products	none known
Hazardous reactions	none known

11. Toxicological Information

Summary

IF SWALLOWED: Large doses may cause stomach distress, nausea or vomiting.

IF IN EYES: causes serious eye damage.

IF ON SKIN: May cause skin irritation, may cause redness and pain. May cause allergic skin reactions.

INHALED: high concentrations of vapours may respiratory irritation and dizziness and drowsiness.

CHRONIC TOXICITY: Ethylbenzene and Xylene vapours may cause reversible damage to kidneys and liver. Prolonged exposure can cause nerve damage (CNS). Xylene may cause damage to foetus possible fetotoxicity, paternal effects. Ethylbenzene is suspected of causing cancer.

Supporting Data

Acute	Oral	Using LD ₅₀ 's for ingredients, the calculated LD ₅₀ (oral, rat) for the mixture is >5,000 mg/kg. Data considered includes: limestone >5000mg/kg, Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines >2000mg/kg bw, xylene 1590 mg/kg (mouse), Bisphenol A epoxy resin 15600mg/kg (mouse), 10.7mL/kg (rat),
--------------	-------------	--

Dermal	ethylbenzene 3500mg/kg (rat), Triethylene tetramine (TETA) 1600 mg/kg bw (mouse). Using LD ₅₀ 's for ingredients, the calculated LD ₅₀ (dermal, rat) for the mixture is >5000 mg/kg. Data considered includes: Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines >2000mg/kg bw, xylene CCID: risk phrase. Gestis: >1700mg/kg, m-xylene: 3228 mg/kg/day (rabbits), Bisphenol A epoxy resin >20mL/kg (rabbit), ethylbenzene data unavailable, Triethylene tetramine (TETA) 550 mg/kg bw (rabbit).
Inhaled	Using LC ₅₀ 's for ingredients, the calculated LC ₅₀ (inhalation, rat) for the mixture is >20mg/L. Data considered includes: xylene 27.6 mg/L (rat, vapour), Bisphenol A epoxy resin not reported, ethylbenzene 9.6mg/L (vapour, rat).
Eye	The mixture is considered to be an eye irritant, because some of the ingredients (bisphenol A, limestone, xylene, ethylbenzene) present are considered eye irritants in more concentrated form. Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines is considered an eye corrosive.
Skin	The mixture is considered to be a skin irritant, because some of the ingredients (bisphenol A, limestone, xylene, ethylbenzene, Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines) present are considered skin irritants in more concentrated form.
Chronic	<p>Sensitisation This mixture is considered a contact sensitiser (bisphenol epoxy resin).</p> <p>Mutagenicity No ingredient present at concentrations > 0.1% is considered a mutagen.</p> <p>Carcinogenicity The mixture is considered to be a suspected carcinogen, because at least one of the ingredients (ethyl benzene) present in greater than 0.1% is suspected to be a carcinogen. Ethylbenzene is possibly carcinogenic to humans (IARC Group 2B). Not classed as carcinogenic in EU.</p>
Reproductive / Developmental	The mixture is considered to be a suspected reproductive or developmental toxicant, because at least one of the ingredients (xylene, ethylbenzene) present in greater than 0.1% is suspected to be a reproductive or developmental toxicant.
Systemic	The mixture is considered to be a suspected target organ toxicant, because at least one of the ingredients (xylene, ethylbenzene) present in greater than 1% is suspected to be a target organ toxicant.
Aggravation of existing conditions	This mixture may affect the CNS if inhaled and cause dizziness and drowsiness. None known.

12. Ecological Data

Summary

This mixture is considered harmful towards aquatic organisms with long lasting effects.

Supporting Data

Aquatic

Using EC₅₀'s for ingredients, the calculated EC₅₀ for the mixture is between 10 mg/L and 100 mg/L. Data considered includes: Fatty acids, C18-unsatd., dimers, reaction products with polyethylenepolyamines 7.07mg/L (96h, Danio rerio (fish)), 5.18mg/L (48hr, Daphnia magna), xylene 8.5mg/l (48hr, Palaemonetes pugio (Crustacea)), 3.3 mg/l (96hr, Oncorhynchus mykiss), 10mg/l (72hr, Skeletonema costatum), Bisphenol A epoxy resin 1.2 mg/L (96h, Oncorhynchus mykiss), 2.7 mg/L (48h, Daphnia magna), ethylbenzene 4.6mg/L (72hr, Selenastrum capricornutum (Algae)), 4.2mg/L (96hr, Oncorhynchus mykiss (Fish, fresh water)), 2.1mg/L (48hr, Daphnia magna (Crustacea)), Triethylene tetramine (TETA) 3.7 mg/l (96hr, Selenastrum capricornutum), 12 mg/l (48hr, Daphnia magna); >101 mg/kg (Adelaius phoenicus).

Bioaccumulation

No data

Degradability

Not readily degradable.

Soil

No evidence of soil toxicity.

Terrestrial vertebrate

Not considered harmful towards terrestrial vertebrates (see acute toxicity)

Terrestrial invertebrate

No evidence toxicity towards terrestrial invertebrates.

Biocidal

no data

Environmental effect levels

No EELs are available for this mixture or ingredients

13. Disposal Considerations

Restrictions	There are no product-specific restrictions, however, local council and resource consent conditions may apply, including requirements of trade waste consents.
Disposal method	Disposal of this product must comply with the Hazardous Substances (Disposal) Notice 2017 and the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore rendered non-hazardous before discharge to the environment.
Contaminated packaging	Disposal of contaminated packaging must comply with the Hazardous Substances (Disposal) Notice 2017 clause 12. Ensure that the package is rendered incapable of containing any substance and is disposed in a manner that is consistent with the requirements of the substance it contained and the material of the package. If possible reuse or recycle packaging.

14. Transport Information

Land Transport Rule: Dangerous Goods 2005 - NZS 5433:2007

There are no specific restrictions for this product (not a dangerous good).

UN number:	NA	Proper shipping name:	NA
Class(es)	NA	Packing group:	NA
Precautions:	NA	Hazchem code:	NA

15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002679, Surface Coatings and Colourants (Toxic [6.7]) Group Standard 2017. All ingredients appear on the NZIoC.

Specific Controls

Key workplace requirements are:

SDS	To be available within 10 minutes in workplaces storing any quantity.
Inventory	An inventory of all hazardous substances must be prepared and maintained.
Packaging	All hazardous substances should be appropriately packaged including substances that have been decanted, transferred or manufactured for own use or have been supplied
Labelling	Must comply with the Hazardous Substances (Labelling) Notice 2017.
Emergency plan	Required if > 1000L is stored.
Certified handler	Not required.
Tracking	Not required.
Bunding & secondary containment	Required if > 1000L is stored.
Signage	Required if > 1000L is stored.
Location compliance certificate	Not required.
Flammable zone	Not required.
Fire extinguisher	Not required.

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

16. Other Information

Abbreviations

Approval Code	Approval HSR002679, Surface Coatings and Colourants (Toxic [6.7]) Group Standard 2017 Controls, EPA. www.epa.govt.nz
CAS Number	Unique Chemical Abstracts Service Registry Number
Ceiling	Ceiling Exposure Value: The maximum airborne concentration of a biological or chemical agent to which a worker may be exposed at any time.
Controls Matrix	List of default controls linking regulation numbers to Matrix code (e.g. T1, I16).
EC₅₀	Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test population (e.g. daphnia, fish species)
EPA	Environmental Protection Authority (New Zealand)
HAZCHEM Code	Emergency action code of numbers and letters that provide information to emergency services, especially fire fighters
HSNO	Hazardous Substances and New Organisms (Act and Regulations)
IARC	International Agency for Research on Cancer
LEL/UEL	Lower Explosive Limit/ Upper Explosive Limit
LD₅₀	Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).
LC₅₀	Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population (usually rats)
MSDS (SDS)	Material Safety Data Sheet (or Safety Data Sheet)
NZIoC	New Zealand Inventory of Chemicals
PES	Prescribed Exposure Standard means a WES or a biological exposure standard that is prescribed in a regulation, a safe work instrument or an approval under HSNO (including group standards).
STEL	Short Term Exposure Limit - The maximum airborne concentration of a chemical or biological agent to which a worker may be exposed in any 15 minute period, provided the TWA is not exceeded
TWA	Time Weighted Average – generally referred to WES averaged over typical work day (usually 8 hours)
UN Number	United Nations Number
WES	Workplace Exposure Standard - The airborne concentration of a biological or chemical agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring using procedures that gather air samples in the worker's breathing zone.

References

Data	Unless otherwise stated comes from the EPA HSNO chemical classification information database (CCID).
Controls	EPA notices, www.epa.govt.nz , Health and Safety at Work (Hazardous Substances) Regulations 2017, www.legislation.govt.nz
WES	The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available on their web site – www.worksafe.govt.nz .
Other References:	Suppliers SDS, EU ECHA, ingredients SDS's, ChemIDplus

Review

Date	Reason for review
July 2018	Not applicable – new SDS

Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely HSNO classifications for this SDS have been estimated based on general information from the supplier (e.g., hazard, toxicological). Full formulation details were not available. This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: +64 9 940 30 80.

