

NOTE:
 Ensure cross-ventilation within the roof structure
 E.G. use of a Castellated Batten directly under the Ply substrate or drill 20mm holes at top of timber supports

NOTE: How many vents?
 Refer Viking Technical Note Venting .

NOTE:
 Substrate to comply with current Viking Roofspec Masterspec specification
 Substrate Checksheet available from www.vikingroofspec.co.nz

Viking 215mm high roof vent IMV111, 120mm high roof vent IMV113, installed as per manufacturers instructions. Colour cap specified (white, black, grey)

Stainless Steel Hose Clamp with Viking Sealant STP870 Water Cut-off Mastic

Substrate

Airflow
w

Airflow

Airflow

Airflow
w

Viking Enviroclad TPO waterproofing membrane 1.52 mm thick, install as per manufacturers instructions

NOTE: Venting not required if specifying Viking WarmRoof or WarmSpan systems

DRAWING TITLE

Viking Enviroclad
 Ventilation Aluminium Cavity Vent

NOTES:

* Angle fillets are not required at upstands for Enviroclad
 * All fixings, cladding and structure are indicative only unless notated



Enviroclad systems are CodeMarked

DRAWING

INFORMATION ONLY

Scale:	Date:	Drawn:	Viking
Not to Scale	23/11/2020		

Detail Ref: **VIK_ENV_020A_VENTROOF**

