



Viking Enviroclad TPO waterproofing membrane 1.52 mm

Viking Cover Board

Viking PIR Polyiso Insulation

Viking Vapour Barrier

Substrate as specified

Mechanically fix S/S or Alum return angle as Diverter. To finish 10mm out from cladding face.

Cladding and underlay to cover membrane upstand 50mm min.

Cladding underlay

Cladding

Continue membrane 150mm

Mechanically fix S/S or Alum return angle as Diverter. To finish 10mm out from cladding face.

Continue Membrane 150mm

**NOTE:**  
 Substrate to comply with current Viking Roofspec Masterspec specification  
 Substrate Checksheet available from [www.vikingroofspec.co.nz](http://www.vikingroofspec.co.nz)

DRAWING TITLE

Viking WS2 - Enviroclad  
 Verge\_edge with wall returning, Diverter for cladding

NOTES:

\* Angle fillets are not required at upstands for Enviroclad  
 \* All fixings, cladding and structure are indicative only unless noted  
 \* All details to be read in conjunction with Viking Specifications

Substrate and structure are indicative only

DRAWING STATUS

INFORMATION ONLY

Scale: Not to Scale	Date: 01/10/2022	Drawn: Viking
Detail Ref: <b>VIK_WS2_ENV_033A_VERGEDGE</b>		