

1. Identification of Substance & Company

Product

Product name	Pitched Roofing Sealant	
Other names	CT Sealant bitumen	
Product code	SES013	
HSNO approval	HSR002662	
Approval description	Surface coatings and Colourants (Flammable) Group Standard 2017	
UN number	1133	
DG class	3	
Proper Shipping Name	ADHESIVES	
Packaging group	III	
Hazchem code	3Y	
Uses	Bitumen Sealant	

Company Details

Company	Viking Roofspec	
Physical Address	80 Alexander Crescent Otara Auckland New Zealand	PO Box 14 451 Panmure Auckland 1741 New Zealand
Telephone	0800 729 799	
Fax	0800 729 788	
Website	www.vikingroofspec.co.nz	

Emergency Telephone Number: 0800 764 766

2. Hazard Identification

Approval

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002662, Surface coatings and Colourants (Flammable) Group Standard 2017). The substance has been classified as hazardous according to the criteria in the Hazardous substances (Minimum Degrees of Hazard) Notice 2017.

Classes

3.1C
6.3B
6.4A
6.9B (narcotic)
9.1D

Hazard Statements

H226 - Flammable liquid and vapour.
H316 - Causes mild skin irritation.
H320 - Causes eye irritation.
H336 - May cause drowsiness or dizziness.
H402 - Harmful to aquatic life.

SYMBOLS

WARNING



Other Classifications

There are no other classifications that are known to apply.

Precautionary Statements

P103 - Read label before use.
P210 - Keep away from ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing vapours.
P264 - Wash hands thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection*.
 P332+P313 - If skin irritation occurs: Get medical advice/ attention.
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337+P313 - If eye irritation persists: Get medical advice/attention.
 P304+P340 - IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
 P312 - Call a POISON CENTRE or doctor/physician if you feel unwell.
 P403+P235 - Store in a well-ventilated place. Keep cool.
 P405 - Store locked up.

3. Composition / Information on Ingredients

Component	CAS/ Identification	Conc (%)
n-butyl acetate	123-86-4	10-30%
Modified Liquid Asphalt	8052-42-4	balance

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

4. First Aid

General Information

If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service).

Recommended first aid facilities Ready access to running water is required. Accessible eyewash is required.

Exposure

Swallowed Do NOT induce vomiting. Give a glass of water to drink. Contact a doctor.
Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact IF ON SKIN: wash with plenty of water. If skin irritation occurs: Get medical advice/attention
Inhaled IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

Advice to Doctor

Treat symptomatically

5. Firefighting Measures

Fire and explosion hazards: Vapours may form an explosive mixture in air which can be ignited by many sources such as pilot lights, open flames, electrical motors, switches and static electricity.
Suitable extinguishing substances: Carbon dioxide, extinguishing powder, foam.
Unsuitable extinguishing substances: Unknown.
Products of combustion: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water. May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying spaces, forming potentially explosive mixtures.
Protective equipment: Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat and eye protection.
Hazchem code: 3Y

6. Accidental Release Measures

Containment If greater than 1000L is stored, secondary containment and emergency plans to manage any potential spills must be in place. In all cases design storage to prevent discharge to storm water.
Emergency procedures In the event of spillage alert the fire brigade to location and give brief description of hazard. Stop the source of the leak, if safe to do so. Shut off all possible sources of ignition. Wear protective equipment to prevent skin, eye and respiratory exposure. Clear area of any unprotected personnel. Contain using sand, earth or vermiculite. Do not use sawdust. Prevent by whatever means possible any spillage from entering drains, sewers,

Clean-up method	or water courses. (If this occurs contact your regional council immediately). Use absorbent (soil, sand or other inert material). Rags are not recommended for the clean-up of spills, as they may create fire or environmental hazard. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.
Disposal	Mop up and collect recoverable material into labelled containers for recycling or salvage. Recycle containers wherever possible. This material may be suitable for approved landfill. Dispose of only in accord with all regulations.
Precautions	Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation.

7. Storage & Handling

Storage	Avoid storage of harmful substances with food. Store out of reach of children. Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames. Avoid contact with incompatible substances as listed in Section 10. Location compliance certificates must be available if storing >1500L (containers >5L), 500L (containers ≤5L), 250L (in use). Containers (and outer packaging) must bear the prescribed labelling, including the Hazchem code, UN number, flammability warning and name of contents.
Handling	Keep exposure to a minimum, and minimise the quantities kept in work areas. See section 8 with regard to personal protective equipment requirements.

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m³ for respirable particulates and 10mg/m³ for inhalable particulates when limits have not otherwise been established.

NZ Workplace Exposure Stds	Ingredient	WES-TWA*	WES-STEL
	modified liquid asphalt	5mg/m ³	data unavailable
	n-butyl acetate	150ppm, 713mg/m ³	200ppm, 950mg/m ³

* These workplace exposure standards are also Prescribed Exposure Standards (PES) under the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016.

Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

Personal Protective Equipment

Eyes



Avoid contact with eyes. Use safety glasses and or chemical splash goggles if splashes are possible. Select eye protection in accordance with AS/NZS 1337.

Skin

If discomfort is felt (e.g., if pre-existing conditions exist, such as dermatitis, cuts or sensitive skin), gloves may be helpful. If you suffer from dermatitis type skin conditions, use gloves. Nitrile gloves are recommended. Protective gloves or suitably resistant material must comply with AS 2161. Replace frequently. Gloves should be checked for tears or holes before use.

Respiratory

A respirator when airborne concentrations approach the WES (section 8). Respirators must have filters appropriate to the duty and comply with AS/NZS1716 and selected, used and maintained in accordance with AS/NS 1715. Use a respirator with an organic vapour cartridge. If using a respirator, ensure that the cartridges are correct for the potential air contamination and are in good working order. Fit testing and clear guidelines and training for use and maintenance of PPE are necessary.

WES Additional Information

Not applicable

9. Physical & Chemical Properties

Appearance	viscous liquid (various colours)
Odour	solvent like odour
pH	no data
Vapour pressure	no data
Viscosity	no data
Boiling point	no data
Volatile materials	38%
Freezing / melting point	no data
Solubility	insoluble in water
Specific gravity / density	0.93g/cm ³
Flash point	23-60°C
Danger of explosion	no data
Auto-ignition temperature	no data
Upper & lower flammable limits	no data
Corrosiveness	non corrosive

10. Stability & Reactivity

Stability	Stable
Conditions to be avoided	Flammable substance. Keep away from sources of ignition at all times. Containers should be kept closed in order to avoid contamination.
Incompatible groups	Strong acids and bases. Oxidising agents.
Substance Specific Incompatibility	none known
Hazardous decomposition products	Oxides of carbon.
Hazardous reactions	none known

11. Toxicological Information

Summary

IF IN EYES: may cause eye irritation.

IF ON SKIN: may cause mild skin irritation. May dry out the skin and cause cracking.

IF INHALED: may cause dizziness and drowsiness.

Supporting Data

Acute	Oral	Using LD ₅₀ 's for ingredients, the calculated LD ₅₀ (oral, rat) for the mixture is >5,000 mg/kg. Data considered includes: n-butyl acetate 3200 mg/kg (rabbit), n-Butyl acetate may be an aspiration hazard, but this mixture has a high viscosity.
	Dermal Inhaled	No evidence of dermal toxicity. Using LC ₅₀ 's for ingredients, the calculated LC ₅₀ (inhalation, rat) for the mixture is >5mg/L (mist). Data considered includes: n-butyl acetate 2 mg/l (rat, dust/mist).
	Eye	The mixture is considered to be an eye irritant, because some of the ingredients (n-butyl acetate) present are considered eye irritants in more concentrated form.
	Skin	The mixture is considered to be a skin irritant, because some of the ingredients (n-butyl acetate) present are considered skin irritants in more concentrated form.
Chronic	Sensitisation	No ingredient present at concentrations > 0.1% is considered a sensitizer.
	Mutagenicity	No ingredient present at concentrations > 0.1% is considered a mutagen.
	Carcinogenicity	No ingredient present at concentrations > 0.1% is considered a carcinogen.
	Reproductive / Developmental	No ingredient present at concentrations > 0.1% is considered a reproductive or developmental toxicant or have any effects on or via lactation.
	Systemic Aggravation of existing conditions	No ingredient present at concentrations > 1% is considered a target organ toxicant. None known.

12. Ecological Data

Summary

This mixture may be harmful towards aquatic organisms.

Supporting Data

Aquatic	Using EC ₅₀ 's for ingredients, the calculated EC ₅₀ for the mixture is between 1 and 100 mg/L. Data considered includes: n-butyl acetate 18 mg/l (96hr, Fathead minnow), 32 mg/l (48hr, Brine shrimp).
Bioaccumulation	No data
Degradability	No data
Soil	No evidence of soil toxicity.
Terrestrial vertebrate	This mixture is not considered harmful towards terrestrial vertebrates.
Terrestrial invertebrate	No evidence of toxicity towards terrestrial invertebrates.
Biocidal	no data
Environmental effect levels	No EELs are available for this mixture or ingredients

13. Disposal Considerations

Restrictions	There are no product-specific restrictions, however, local council and resource consent conditions may apply, including requirements of trade waste consents.
Disposal method	Disposal of this product must comply with the Hazardous Substances (Disposal) Notice 2017 and the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore rendered non-hazardous before discharge to the environment.
Contaminated packaging	Disposal of contaminated packaging must comply with the Hazardous Substances (Disposal) Notice 2017 clause 12. Ensure that the package is rendered incapable of containing any substance and is disposed in a manner that is consistent with the requirements of the substance it contained and the material of the package. If possible reuse or recycle packaging.

14. Transport Information

Land Transport Rule: Dangerous Goods 2005 - NZS 5433:2007

Transport according to NZS 5433 (Transport of Hazardous Substances on Land). Considered a dangerous good for transport.

UN number:	1133	Proper shipping name:	ADHESIVES
Class(es)	3	Packing group:	III
Precautions:	FLAMMABLE LIQUID	Hazchem code:	3Y

15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002662, Surface coatings and Colourants (Flammable) Group Standard 2017. All ingredients appear on the NZIoC.

Specific Controls

Key workplace requirements are:

SDS	To be available within 10 minutes in workplaces storing any quantity.
Inventory	An inventory of all hazardous substances must be prepared and maintained.
Packaging	All hazardous substances should be appropriately packaged including substances that have been decanted, transferred or manufactured for own use or have been supplied
Labelling	Must comply with the Hazardous Substances (Labelling) Notice 2017.
Emergency plan	Required if > 1000L is stored.
Certified handler	Not required.
Tracking	Not required.
Bunding & secondary containment	Required if > 1000L is stored.
Signage	Required if > 1000L is stored in any one location.
Location compliance certificate	Required if > 1500L (containers >5L), 500L (containers ≤5L), 250L (in use) is stored.
Flammable zone	Must be established if > 100L (closed containers), 25L (decanting), 5L (open occasionally), 1L (in use), stored in any one location is stored in any one location.
Fire extinguisher	If > 500L present.

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

16. Other Information

Abbreviations

Approval Code	Approval HSR002662, Surface coatings and Colourants (Flammable) Group Standard 2017 Controls, EPA. www.epa.govt.nz
CAS Number	Unique Chemical Abstracts Service Registry Number
Ceiling	Ceiling Exposure Value: The maximum airborne concentration of a biological or chemical agent to which a worker may be exposed at any time.
Controls Matrix	List of default controls linking regulation numbers to Matrix code (e.g. T1, I16).
EC₅₀	Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test population (e.g. daphnia, fish species)
EPA	Environmental Protection Authority (New Zealand)
HAZCHEM Code	Emergency action code of numbers and letters that provide information to emergency services, especially fire fighters
HSNO	Hazardous Substances and New Organisms (Act and Regulations)
IARC	International Agency for Research on Cancer
LEL/UEL	Lower Explosive Limit/ Upper Explosive Limit
LD₅₀	Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).
LC₅₀	Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population (usually rats)
MSDS (SDS)	Material Safety Data Sheet (or Safety Data Sheet)
NZIoC	New Zealand Inventory of Chemicals
PES	Prescribed Exposure Standard means a WES or a biological exposure standard that is prescribed in a regulation, a safe work instrument or an approval under HSNO (including group standards).
STEL	Short Term Exposure Limit - The maximum airborne concentration of a chemical or biological agent to which a worker may be exposed in any 15 minute period, provided the TWA is not exceeded
TWA	Time Weighted Average – generally referred to WES averaged over typical work day (usually 8 hours)
UN Number	United Nations Number

WES Workplace Exposure Standard - The airborne concentration of a biological or chemical agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring using procedures that gather air samples in the worker's breathing zone.

References

Data Unless otherwise stated comes from the EPA HSNO chemical classification information database (CCID).

Controls EPA notices, www.epa.govt.nz, Health and Safety at Work (Hazardous Substances) Regulations 2017, www.legislation.govt.nz

WES The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available on their web site – www.worksafe.govt.nz.

Other References: Suppliers SDS, EU ECHA, ingredients SDS's, ChemIDplus

Review

Date	Reason for review
July 2018	Not applicable – new SDS

Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely HSNO classifications for this SDS have been estimated based on general information from the supplier (e.g., hazard, toxicological). Full formulation details were not available. This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: +64 9 940 30 80.

