

Viking Roofspec Torch-on  
2 Layer Membrane System

Viking Torch-on CAP sheet 4mm  
thick, install as per manufacturers  
instructions

Viking Torch-on BASE sheet 3mm  
thick, install as per manufacturers  
instructions

Substrate

150 mm membrane  
upstand

Fixing bar

Alum or S/S Angle 50x50mm x 1.6mm  
or thicker. Use fixing bar to secure  
membrane to drip-edge

Continue membrane  
150 mm

Use Viking Proprietary S/S Kick-out  
Diverters IMT604 R/H or IMT605 L/H  
screw fixed

Cladding and underlay to  
cover membrane upstand

Cladding

Cladding underlay


**NOTE:**  
Substrate to comply with current  
Viking Roofspec Masterspec  
specification  
Substrate Checksheet available  
from [www.vikingroofspec.co.nz](http://www.vikingroofspec.co.nz)

DRAWING TITLE

Viking Torch-On  
Verge\_edge with wall continuing, Diverter for cladding.

NOTES:

- Viking Waterproof Membrane as  
notated can be Viking Gemini, Lybra  
or Phoenix Super.
- All fixings, cladding and structure are  
indicative only unless notated.



Viking Torch-On  
systems are  
CodeMarked

DRAWING

INFORMATION ONLY

Scale:	Date:	Drawn:	Viking
Not to Scale	23/11/2020		
Detail Ref: <b>VIK_TOR_033_VERGEDGE</b>			