

Screw fixing of Sump into recessed blocking

Viking Cover Board

Leaf grate

Viking Enviroclad TPO waterproofing membrane 1.52 mm

Overflow insert

NOTE:
 1/ Overflow to match outlet capacity.
 2/ Overflow to be plumbed independent of stormwater, through soffit or exterior wall

Notes:
 Sumps to be plumbed with flexible hose-clamped couplings such as Dux or PlumbQwik

Viking Insulation Plug and Fixing

Viking PIR Polyiso Insulation

Substrate as specified

Viking Vapour Barrier

Viking sump / overflow IMR120T
 TPO weldable, installed as per manufacturers instructions.

NOTE:
 Substrate to comply with current Viking Roofspec Masterspec specification
 Substrate Checksheet available from www.vikingroofspec.co.nz

DRAWING TITLE

Viking WS2 - Enviroclad
 Penetration_Sump Outlet with Overflow

NOTES:

- * Angle fillets are not required at upstands for Enviroclad
- * All fixings, cladding and structure are indicative only unless noted
- * All details to be read in conjunction with Viking Specifications

Substrate and structure are indicative only

DRAWING STATUS

INFORMATION ONLY

Scale: Not to Scale	Date: 01/10/2022	Drawn:	Viking
Detail Ref: VIK_WS2_ENV_003_PENESUMP			