

NOTE:  
 Substrate to comply with current  
 Viking Roofspec Masterspec  
 specification  
 Substrate Checksheet available  
 from [www.vikingroofspec.co.nz](http://www.vikingroofspec.co.nz)

Refer to Table 7  
 E2/AS1

Metal Cap  
 with saddle flashing  
 from under profiled  
 roofing

300 mm flood-board

12mm plywood

Solid blocking

300 mm

17mm plywood

35 mm

Viking Enviroclad TPO  
 waterproofing membrane 1.52  
 mm thick, install as per  
 manufacturers instructions

Viking PIR Polyiso Insulation

Viking Vapour Barrier, install as  
 per manufacturers instructions.

Substrate

150 mm  
 min. upstand

DRAWING TITLE

Viking WarmSpan - Enviroclad  
 Roof Junction\_Dormer Gutter

NOTES:

- \* Angle fillets are not required at upstands for Enviroclad
- \* All fixings, cladding and structure are indicative only unless notated
- \* All details to be read in conjunction with Viking Specifications

WarmSpan System is Branz  
 Appraised - 713

DRAWING

INFORMATION ONLY

Scale:	Date:	Drawn:	Viking
Not to Scale	01/03/2022		

VIK\_WSE\_074A\_RJUNDORM