

Viking Enviroclad TPO waterproofing membrane 1.52 mm thick, install as per manufacturers instructions

Fastenings by other trades not to penetrate membrane

Viking EJOT Mounting Bar

NOTE:
Refer to Ejobar product data sheet for the correct installation for solar mounting panel

EJOT End-Cap

EJOT

NOTE:
Creates a LOW-RISK fixing base for light-weight mechanical and electrical essentials such as pipework and cable trays - through to light weight solar PV and solar thermal installations.
Maximum point load *30kg per/Lm
Maximum uplift 2.8Kn

Viking PIR Polyiso Insulation

Substrate

NOTE:
Substrate to comply with current Viking Roofspec Masterspec specification
Substrate Checksheet available from www.vikingroofspec.co.nz

100 mm

DRAWING TITLE

Viking WarmSpan - Enviroclad
Penetration_EJOT Plinth for Enviroclad

NOTES:

- * Angle fillets are not required at upstands for Enviroclad
- * All fixings, cladding and structure are indicative only unless notated
- * All details to be read in conjunction with Viking Specifications

WarmSpan System is Branz Appraised - 713

DRAWING

INFORMATION ONLY

Scale:	Date:	Drawn:	Viking
Not to Scale	01/03/2022		

Detail Ref: **VIK_WSE_015_PEENEJOT**