

Identification of Substance & Company

Product

Product name Low-VOC untack **Product code** not assigned **HSNO** approval HSR002515

Approval description Aerosols (Flammable) Group Standard 2017

UN number DG class 2.1

Proper Shipping Name CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (Acetone,

Perchlorobenzotrifluoride)

Packaging group NA Hazchem code NA

Uses Adhesive remover/solvent

Company Details

Company Viking Roofspec

Physical Address 80 Alexander Crescent PO Box 14 451 Otara Panmure Auckland Auckland 1741 New Zealand

New Zealand 0800 729 799 **Telephone** Fax 0800 729 788

Website www.vikingroofspec.co.nz

Emergency Telephone Number: 0800 764 766

2. **Hazard Identification**

Approval

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002515, Aerosols (Flammable) Group Standard 2017). The substance has been classified as hazardous according to the criteria in the Hazardous substances (Minimum Degrees of Hazard) Notice 2017.

Hazard Statements Classes

2.1.2A H222 - Extremely flammable aerosol. H303 - May be harmful if swallowed 6.1E (oral) 6.3B H316 - Causes mild skin irritation. 6.4A H320 - Causes eye irritation.

6.5B H317 - May cause an allergic skin reaction. 6.9B (narcotic) H336 - May cause drowsiness or dizziness. 9.1B

H411 - Toxic to aquatic life with long lasting effects.

H423 - Harmful to the soil environment. 9.2C

SYMBOLS

DANGER



There are no other classifications that are known to apply.



Precautionary Statements

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P103 - Read label before use.

P210 - Keep away from ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Pressurized container: Do not pierce or burn, even after use.

P261 - Avoid breathing vapours/spray.

P264 - Wash hands thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/eye protection/face protection*.

P312 - Call a POISON CENTRE or doctor/physician if you feel unwell.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P304+P340 - IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P312 - Call a POISON CENTRE or doctor/physician if you feel unwell.

P391 - Collect spillage.

P410 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

3. Composition / Information on Ingredients

Component	CAS/ Identification	Conc (%)
Acetone	67-64-1	50-75%
4-Chlorobenzotrifluoride	98-56-6	22-40%
D-Limonene	5989-27-5	1-7%

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

4. First Aid

General Information

If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service).

Recommended first aid Ready access to running water is required. Accessible eyewash is required. facilities

Exposure

Inhaled

Swallowed IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. Do NOT

induce vomiting.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical

advice/ attention. Take off contaminated clothing and wash before re-use. IF INHALED: Remove to fresh air and keep at rest in a position comfortable for

breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

Advice to Doctor

Treat symptomatically



5. Firefighting Measures

Fire and explosion hazards: This product is an aerosol that releases flammable vapours. This product has the

potential to cause fire or to create an additional hazard during fire. Buildup of explosive mixtues possible. Container may rupture/explode in a fire. Remove undamaged cans if safe to do so. Leaking or burning cans should be extinguished only when absolutely necessary. Spontaneous or explosive reignition may occur. Extinguish fire in surrounding

area

Suitable extinguishing

substances:

Unsuitable extinguishing

substances:

Unknown.

Products of combustion: Carbon dioxide, and if combustion is incomplete, carbon monoxide, oxides of nitrogen

and smoke. Water. May form toxic mixtures in air and may accumulate in sumps, pits

and other low-lying spaces, forming potentially explosive mixtures.

Carbon dioxide, extinguishing powder, foam, fog sprays, water jets.

Protective equipment: Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat

and eye protection.

Hazchem code: Not applicable for Aerosol. Liquid has Hazchem code: 3YE.

6. Accidental Release Measures

Containment If greater than 1000L is stored, secondary containment and emergency plans to manage

any potential spills must be in place. In all cases design storage to prevent discharge to

storm water.

Emergency procedures In the event of spillage alert the fire brigade to location and give brief description of

hazard. Stop the source of the leak, if safe to do so. Shut off all possible sources of ignition. Wear protective equipment to prevent skin, eye and respiratory exposure. Clear area of any unprotected personnel. Contain using sand, earth or vermiculite. Prevent by whatever means possible any spillage from entering drains, sewers, or water courses. (If

this occurs contact your regional council immediately).

Clean-up method Collect undamaged cans and recycle. Collect damaged cansand seal in properly labelled

containers or drums for disposal.

Disposal Collect recoverable material into labelled containers for recycling or salvage. This

material may be suitable for approved landfill. Dispose of only in accord with all

regulations.

Precautions Wear protective equipment to prevent skin and eye contamination and the inhalation of

vapours. Work up wind or increase ventilation. Be aware of fire risk - avoid sources of

ignition.

7. Storage & Handling

Storage Avoid storage of harmful substances with food.

Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames. Keep out of direct sunlight. Avoid contact with incompatible substances as listed in Section 10.

Keep out of reach of children.

Handling Keep exposure to a minimum, and minimise the quantities kept in work areas. See

section 8 with regard to personal protective equipment requirements. Avoid skin and eye

contact and inhalation of vapour, mist or aerosols.

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m³ for respirable particulates and 10mg/m³ for inhalable particulates when limits have not otherwise been established.

NZ Workplace Ingredient WES-TWA* WES-STEL

Exposure Stds acetone 500ppm, 1185mg/m³ 1000ppm, 2375 mg/m³

Product Name: Low-VOC untack



Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

Personal Protective Equipment

Taking care of detail

Eyes



Avoid contact with eyes. Use safety glasses and or chemical splash goggles if splashes are possible. Select eye protection in accordance with AS/NZS 1337.

Skin



Avoid any skin contact. Wear overalls, rubber boots and impervious gloves. Nitrile, teflon or PVA gloves are recommended. Protective gloves or suitably resistant material must comply with AS 2161. Replace frequently. Gloves should be checked for tears or holes before use. Protective clothing must comply with AS 2919, AS3765.1 or AS3765.2. PVC or rubber boots must comply with AS/NZS 2210.2 and selected and maintained in accordance with AS/NS2210.1. Remove protective clothing and wash exposed areas with soap and water prior to eating, drinking or smoking.

Respiratory



A respirator when airborne concentrations approach the WES (section 8). Respirators must have filters appropriate to the duty and comply with AS/NZS1716 and selected, used and maintained in accordance with AS/NS 1715. Use a respirator with an organic vapour cartridge. If using a respirator, ensure that the cartridges are correct for the potential air contamination and are in good working order. Fit testing and clear guidelines and training for use and maintenance of PPE are necessary.

WES Additional Information

Not applicable

9. **Physical & Chemical Properties**

Appearance thin, water-white liquid

solvent odour Odour Not available Ha Vapour pressure not available **Viscosity** no data **Boiling point** 56.1°C Volatile materials 33g/L Freezing / melting point no data

Solubility insoluble in water Specific gravity / density 0.899 g/mL Flash point -20°C **Danger of explosion** no data **Auto-ignition temperature** no data **Upper & lower flammable limits** no data Corrosiveness non corrosive

10. **Stability & Reactivity**

Stability

Conditions to be avoided

Flammable substance. Keep away from sources of ignition at all times. Containers should be kept closed in order to avoid contamination.

Incompatible groups Oxidisers, strong acids, bases. **Substance Specific**

Incompatibility

none known

Hazardous decomposition

Oxides of carbon

products **Hazardous reactions**

none known



Toxicological Information 11.

Summary

IF SWALLOWED: can result in nausea, vomiting and central nervous system depression. If the victim is uncoordinated there is greater likelihood of vomit entering the lungs and causing subsequent acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death.

IF IN EYES: may cause eye irritation.

Inhaled

IF ON SKIN: may cause skin irritation. Repeated or prolonged contact may cause drying out of the skin resulting in nonallergic dermatitis. Sensitised individuals may experience an allergic skin reaction.

INHALED: high concentrations of vapours may cause dizziness and drowsiness.

Supporting Data

Using LD_{50} 's for ingredients, the calculated LD_{50} (oral, rat) for the mixture is between Acute Oral

2000 and 5000 mg/kg. Data considered includes: acetone 3000 mg/kg (mouse), 4-

Chlorobenzotrifluoride 5546 mg/kg (rat), D-limonene 4400mg/kg (rat).

Using LD₅₀'s for ingredients, the calculated LD₅₀ (dermal, rat) for the mixture is >5000 **Dermal**

mg/kg. Data considered includes: 4-Chlorobenzotrifluoride >3300mg/kg (rabbit).

Using LC50's for ingredients, the calculated LC50 (inhalation, rat) for the mixture is >5,000

ppm. Data considered includes: 4-Chlorobenzotrifluoride > 32.03 mg/l (rat). Eye The mixture is considered to be an eye irritant, because some of the ingredients present

are considered eye irritants in more concentrated form.

Skin The mixture is considered to be a skin irritant, because some of the ingredients present

are considered skin irritants in more concentrated form.

Chronic Sensitisation The mixture is considered to be a contact sensitizer. D-Limonene is considered a skin

sensitiser.

Mutagenicity No ingredient present at concentrations > 0.1% is considered a mutagen. Carcinogenicity No ingredient present at concentrations > 0.1% is considered a carcinogen. Reproductive / No ingredient present at concentrations > 0.1% is considered a reproductive or

Developmental developmental toxicant or have any effects on or via lactation.

No ingredient present at concentrations > 1% is considered a target organ toxicant. **Systemic**

Inhalation of vapours may cause dizziness and drowsiness.

Aggravation of existing conditions None known.

12. **Ecological Data**

Summary

This mixture may be toxic towards aquatic organisms with long lasting effects and harmful towards soil organisms.

Supporting Data

Aquatic Using EC50's for ingredients, the calculated EC50 for the mixture is between 1 mg/L and

> 10 mg/L. Data considered includes: 4-Chlorobenzotrifluoride LC₅₀: 3mg/L (96h, Danio rerio (zebra fish)), EC50: 2mg/L (48h, Daphnia magna), NOEC: 0.41mg/L (72h, Pseudokirchneriella subcapitata (green algae)) D-limonene 0.702 mg/l (96hr, fish),

0.421mg/L (48 hr, Crustacean), 0.719 mg/L (72hr, Algal).

Bioaccumulation No data Degradability No data

Soil This mixture may be harmful to the soil environment. D-Limonene is classed 9.2B by

EPA.

Terrestrial vertebrate This mixture is not classed as 9.3. See acute toxicity. Terrestrial invertebrate No evidence of toxicity towards terrestrial invertebrates.

Biocidal no data

13. **Disposal Considerations**

Restrictions There are no product-specific restrictions, however, local council and resource consent

conditions may apply, including requirements of trade waste consents.

Disposal method Disposal of this product must comply with the Hazardous Substances (Disposal) Notice

2017 and the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore

rendered non-hazardous before discharge to the environment.

Disposal of contaminated packaging must comply with the Hazardous Substances Contaminated packaging (Disposal) Notice 2017 clause 12. Ensure that the package is renedered incapable of

containing any substance and is disposed in a manner that is consistent with the

Page 5 of 7 March 2019

Product Name: Low-VOC untack



requirements of the substance it contained and the material of the package. If possible reuse or recycle packaging.

14. Transport Information

Land Transport Rule: Dangerous Goods 2005 - NZS 5433:2007

Transport according to NZS 5433 (Transport of Hazardous Substances on Land). Considered a dangerous good for

transport.

UN number: 3501 **Proper shipping name:** CHEMICAL UNDER PRESSURE,

FLAMMABLE, N.O.S. (Acetone,

Perchlorobenzotrifluoride)

Class(es) 2.1 Packing group: NA
Precautions: Flammable aerosol Hazchem code: NA

15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002515, Aerosols (Flammable) Group Standard 2017 .

All Ingredients appear on the NZIoC.

Specific Controls

Key workplace requirements are:

SDS To be available within 10 minutes in workplaces storing any quantity.

Inventory An inventory of all hazardous substances must be prepared and maintained.

Packaging All hazardous substances should be appropriately packaged including substances

that have been decanted, transferred or manufactured for own use or have been

supplied

Labelling Must comply with the Hazardous Substances (Labelling) Notice 2017.

Emergency plan Required if > 1000L is stored.

Certified handler Not required. Tracking Not required.

Bunding & secondary containment
Signage
Required if > 1000L is stored.
Required if > 1000L is stored.
Required if > 3000L is stored.
Required if > 3000L is stored.

Flammable zone Must be established if > 3000L is stored.

Fire extinguisher If > 3000L present.

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

16. Other Information

Abbreviations

Approval Code Approval HSR002515, Aerosols (Flammable) Group Standard 2017 Controls, EPA.

www.epa.govt.nz

CAS Number Unique Chemical Abstracts Service Registry Number

Ceiling Exposure Value: The maximum airborne concentration of a biological or chemical

agent to which a worker may be exposed at any time.

Controls MatrixList of default controls linking regulation numbers to Matrix code (e.g. T1, I16). **EC**50
Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test

population (e.g. daphnia, fish species)

EPA Environmental Protection Authority (New Zealand)

HAZCHEM Code Emergency action code of numbers and letters that provide information to emergency

services, especially fire fighters

HSNO Hazardous Substances and New Organisms (Act and Regulations)

IARC International Agency for Research on Cancer
LEL/UEL Lower Explosive Limit/ Upper Explosive Limit

LD₅₀ Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).

LC₅₀ Lethal Concentration 50% − concentration in air which is fatal to 50% of a test population

(usually rats)

MSDS (SDS) Material Safety Data Sheet (or Safety Data Sheet)

Page 6 of 7 March 2019

Product Name: Low-VOC untack



NZIoC New Zealand Inventory of Chemicals

PES Prescribed Exposure Standard means a WES or a biological exposure standard that is

prescribed in a regulation, a safe work instrument or an approval under HSNO (including

group standards).

STEL Short Term Exposure Limit - The maximum airborne concentration of a chemical or

biological agent to which a worker may be exposed in any 15 minute period, provided the

TWA is not exceeded

TWA Time Weighted Average – generally referred to WES averaged over typical work day

(usually 8 hours)

UN Number United Nations Number

WES Workplace Exposure Standard - The airborne concentration of a biological or chemical

agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring

using procedures that gather air samples in the worker's breathing zone.

References

Unless otherwise stated comes from the EPA HSNO chemical classification information

database (CCID).

Controls EPA notices, www.epa.govt.nz, Health and Safety at Work (Hazardous Substances)

Regulations 2017, www.legislation.govt.nz

WES The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available

on their web site – www.worksafe.govt.nz.

Other References: Suppliers SDS, EU ECHA, ingredients SDS's, ChemIDplus

Review

DateReason for reviewMarch 2019Not applicable – new SDS

Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely HSNO classifications for this SDS have been estimated based on general information from the supplier (e.g., hazard, toxicological). This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: +64 9 940 30 80.

