

NOTE:
Refer to Safety Anchor supplier for specific fixing requirements

Fire test ISO9705
Viking WarmSpan system is rated 1 - S

PBI Anchor system supplied and installed by PBI Height Safety
Anchor base dimension 440x350

Bitumen Sealant fully surrounding PBI anchor base
Supplied and installed by PBI Height Safety

14G x 50mm Tek Screws with compression washer
to provide watertight seal supplied and installed by PBI

Bitumen Compatible Sealant
Viking SES015 Elastigum

Viking Torch-on
Cap Sheet Membrane

Viking Torch-on
Base Sheet Membrane

Viking PIR Polyiso Insulation sheet

Fixings to be determined by Anchor supplier

Structural support for Anchor Plinth

Viking Vapour Barrier Tape
required for Climate Zone 3

Substrate and fixings to comply with current Viking
Roofspec WarmSpan Masterspec specification

Purlin or structural support for substrate



DRAWING TITLE
Viking WarmSpan with Viking Torch-on 2 layer membrane System PBI Anchor Plinth

NOTES:
Substrate Indicative Only

DRAWING STATUS			
INFORMATION ONLY			
Not to Scale	DATE 05/06/2018	Detail Ref.	ISSUE
DRAWN Viking		VWS16VT	A