



NOTE:
 Substrate to comply with current Viking
 Roofspec Masterspec specification
 Substrate Checksheet available from
www.vikingroofspec.co.nz

IMPORTANT NOTES for all following details:

- Specification:** These details are for use with all Viking Torch-on Membranes Gemini APP, Lybra SBS or Phoenix Super APAO selections. Contact Viking Roofspec to assist with the best selection for your needs.
- Priming:** All substrates and surfaces where Torch-on membrane is being applied must be primed with Viking SES300 Bituminous primer. All Metal flashings or Proprietary fittings such as drip-edges, drains, sumps and scuppers must be sanded then primed with Viking Solvent-based Bituminous Primer SES297.
- Substrates:** All Substrates are to comply with Viking Torch-on System requirements. All external corners must be min. 5mm radius, with Internal corners to have min. 20mm Angle Fillet installed. A Bitumen Fillet is best.
- Detailing:** All upstand transitions are to be installed as per this detail for Internal gutters, door thresholds, wall upstands, skylight upstands etc. Reasoning: To allow for membrane movement near fillets at substrate transition from horizontal to vertical planes

DRAWING TITLE

Viking Torch-On
 Specification Requirements

NOTES:

- Viking Waterproof Membrane as notated can be Viking Gemini, Lybra or Phoenix Super.
- All fixings, cladding and structure are indicative only unless notated.



Viking Torch-On
 systems are
 CodeMarked

DRAWING

INFORMATION ONLY

Scale:	Date:	Drawn:	Viking
Not to Scale	23/11/2020		
Detail Ref:			

VIK_TOR_000_NOTES003