

SET153 Gasket

SMT076V Lap Tape

Viking Roofspec Architectural Finishing Series IMT700/701 barge flashing, installed as per manufacturers instructions.

Cladding system as designed by others

NOTE: Viking AFS Barge Flashings are angled to suit 5° slope to the top of Parapet or Barge. For slopes greater than 5° modifications to these flashings or allow 6 weeks pre-order with Roofspec.

3° to 5° Slope
40 mm

Viking Enviroclad TPO waterproofing membrane 1.52 mm

Viking Cover Board

Viking PIR Polyiso Insulation

NOTE:
Substrate to comply with current Viking Roofspec Masterspec specification
Substrate Checksheet available from www.vikingroofspec.co.nz

Substrate as specified

Viking Insulation Plug and Fixing

Viking Vapour Barrier

DRAWING TITLE

Viking WS2 - Enviroclad
Verge_Barge with Low Profile AFS

NOTES:

- * Angle fillets are not required at upstands for Enviroclad
- * All fixings, cladding and structure are indicative only unless noted
- * All details to be read in conjunction with Viking Specifications

Substrate and structure are indicative only

DRAWING STATUS

INFORMATION ONLY

Scale: Not to Scale	Date: 01/10/2022	Drawn: Viking
Detail Ref: VIK_WS2_ENV_031_VERGBARG		

