# SeamlesSeal Ultra HSLV



## Safety Data Sheet

## . Oldentification of Substance & Company

#### **Product**

Product name Product code HSNO approval Approval description

UN number DG class Proper Shipping Name Packaging group Hazchem code Uses

#### **Company Details**

Company Physical Address

Telephone Fax Website SeamlesSeal Ultra HSLV not assigned HSR002670, Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020 NA NA NA NA NA Silicone Roof Coating

Viking Roofspec 80 Alexander Crescent Otara Auckland New Zealand 0800 729 799 0800 729 788 www.vikingroofspec.co.nz

PO Box 14 451 Panmure Auckland 1741 New Zealand

## Emergency Telephone Number: 0800 764 766

2. Hazard Identification

#### Approval

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002670, Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020). The substance has been classified as hazardous according to the criteria in the Hazardous substances (Hazard Classification) Notice 2020.

#### **GHS 7 Classes**

Eye irritant category 2 Skin sensitiser category 1 Reproductive toxicity category 2 STOT\* single exposure category 3 STOT\* single exposure category 3

\*STOT – system target organ toxicity



#### **Hazard Statements**

| H319 - Causes serious eye irritation.                       |
|---|
| H317 - May cause an allergic skin reaction.                 |
| H361 - Suspected of damaging fertility or the unborn child. |
| H335 - May cause respiratory irritation.                    |
| H336 - May cause drowsiness or dizziness.                   |
|   |

#### **Other Classifications**

There are no other classifications that are known to apply.

NOTE: This substance does contain quartz silica. It is present in the liquid and not considered respirable. Respirable crystalline silica dust may potentially be released from this substance after it has cured. e.g. sanding, cutting, grinding.

SeamlesSeal Ultra HSLV Safety Data Sheet



**Precautionary Statements** 

| Prevention | <ul> <li>P103 - Read label before use.</li> <li>P201 - Obtain special instructions before use.</li> <li>P202 - Do not handle until all safety precautions have been read and understood.</li> <li>P261 - Avoid breathing vapours.</li> <li>P264 - Wash hands thoroughly after handling.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> <li>P272 - Contaminated work clothing should not be allowed out of the workplace.</li> <li>P280 - Wear protective gloves/eye protection/face protection.</li> </ul>  |
|------------|---|
| Response   | <ul> <li>P308+P313 - IF exposed or concerned: Get medical advice/ attention.</li> <li>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P337+P313 - If eye irritation persists: Get medical advice/attention.</li> <li>P302+P352 - IF ON SKIN: Wash with plenty of soap and water.</li> <li>P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.</li> <li>P363 - Wash contaminated clothing before reuse.</li> <li>P304+P340 - IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.</li> <li>P312 - Call a POISON CENTRE or doctor/physician if you feel unwell.</li> </ul> |
| Storage    | P403+P233 - Store in a well-ventilated place. Keep container tightly closed.<br>P405 - Store locked up.   |
| Disposal   | P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.   |

## 3. Composition / Information on Ingredients

| Component                                  | CAS/ Identification | Concentration |
|--|---------------------|---------------|
| Dimethylsiloxane, hydroxyl terminated      | 70131-67-8          | 50-60%        |
| Quartz (SiO2)                              | 14808-60-7          | 20-30%        |
| Titanium dioxide                           | 13463-67-7          | 5-10%         |
| Methyl-O,O',O''-butan-2-on-trioximo-silane | 22984-54-9          | 5-10%         |
| Octamethylcyclotetrasiloxane               | 556-67-2            | 1-5%          |

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

## 4. First Aid

### **General Information**

If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel<br/>that you may have been harmed or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency<br/>service).Recommended first aid<br/>facilitiesReady access to running water is required. Accessible eyewash is required.

| Exposure     |  |
|--------------|--|
| Swallowed    | IF SWALLOWED: Call a POISON CENTRE or doctor/physician if you feel unwell. Rinse mouth. Do NOT induce vomiting. Give a glass of water to drink.  |
| Eye contact  | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if<br>present and easy to do. Continue rinsing. If eye irritation persists: Get medical<br>advice/attention.   |
| Skin contact | IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash before re-use.   |
| Inhaled      | Generally, inhalation of vapours is unlikely to result in adverse health effects. If coughing, dizziness or shortness of breath is experienced, remove the patient to fresh air immediately. If patient is unconscious, place in the recovery position (on the side) for transport and contact a doctor. |
|              |  |

## Advice to Doctor

Treat symptomatically.

## SeamlesSeal Ultra HSLV Safety Data Sheet



|   | 5. Firefighting Measures  |
|---|---|
| Fire and explosion hazards:<br>Suitable extinguishing<br>substances:<br>Unsuitable extinguishing<br>substances: | There are no specific risks for fire/explosion for this chemical. It is non-flammable.<br>Carbon dioxide, extinguishing powder or water jet. Fight larger fires with water jet or<br>alcohol resistant foam.<br>Unknown.  |
| Products of combustion:   | Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water.<br>May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying<br>spaces, forming potentially explosive mixtures.   |
| Protective equipment:<br>Hazchem code:  | Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat and eye protection.<br>NA   |
|   | 6. Accidental Release Measures  |
| Containment   | If greater than 1000L is stored, secondary containment and emergency plans to manage<br>any potential spills must be in place. In all cases design storage to prevent discharge to<br>storm water.  |
| Emergency procedures  | In the event of spillage alert the fire brigade to location and give brief description of hazard.<br>Stop the source of the leak, if safe to do so. Wear protective equipment to prevent skin, eye and respiratory exposure. Clear area of any unprotected personnel. Contain using sand, earth or vermiculite. Do not use sawdust. Prevent by whatever means possible any spillage from entering drains, sewers, or water courses. (If this occurs contact your regional council immediately). |
| Clean-up method   | Use absorbent (soil, sand or other inert material). Rags are not recommended for the clean-up of spills, as they may create fire or environmental hazard. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.  |
| Disposal  | Mop up and collect recoverable material into labelled containers for recycling or salvage.<br>Recycle containers wherever possible. This material may be suitable for approved<br>landfill. Dispose of only in accord with all regulations.   |
| Precautions   | Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation.  |
|   | 7. Storage & Handling   |
| Storage   | Avoid storage of harmful substances with food. Store out of reach of children.<br>Containers should be kept closed in order to minimise contamination. Keep from<br>extreme heat and open flames. Avoid contact with incompatible substances as listed in<br>Section 10.  |
| Handling  | Keep exposure to a minimum, and minimise the quantities kept in work areas. See section 8 with regard to personal protective equipment requirements.  |
| 8   | . Exposure Controls / Personal Protective Equipment   |

irofighting Moo

## Workplace Exposure Standards

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m<sup>3</sup> for respirable particulates and 10mg/m<sup>3</sup> for inhalable particulates when limits have not otherwise been established.

NZ Workplace Exposure Stds Ingredient Quartz (SiO2) Titanium dioxide WES-TWA 0.05mg/m<sup>3</sup> (Respirable) 10mg/m<sup>3</sup> WES-STEL


**Engineering Controls** 

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.





#### **Personal Protective Equipment**



preferred.

#### WES Additional Information

### Not applicable

|  | 9. Physical & Chemical Properties  |
|--|--|
| Appearance<br>Odour<br>Odour Threshold<br>pH<br>Freezing/melting point<br>Boiling Point<br>Flashpoint<br>Flammability<br>Upper & lower flammable limits<br>Vapour pressure<br>Vapour density<br>Specific gravity/density<br>Solubility<br>Partition coefficient<br>Auto-ignition temperature<br>Decomposition temperature<br>Viscosity | Black Liquid<br>mild odour<br>no data<br>no data<br>no data<br>no data<br>>93°C<br>non flammable<br>no LEL or UEL<br>no data<br>no data<br>1.30g/cm3<br>no data<br>no data<br>no data<br>no data |
| Particle Characteristics   | no data<br>10. Stability & Reactivity  |
|  |  |
| Stability<br>Conditions to be avoided  | Stable<br>Containers should be kept closed in order to avoid contamination. Keep from extreme<br>heat and open flames.   |
| Incompatible groups<br>Substance Specific<br>Incompatibility   | Moisture, strong acids, strong bases, oxidising and reducing agents.<br>none known   |
| Hazardous decomposition products   | Oxides of carbon, oxides of nitrogen, oxides of silicone and traces of HCN.  |
| Hazardous reactions  | none known   |

## SeamlesSeal Ultra HSLV Safety Data Sheet



## 11. Toxicological Information

### Summary

IF SWALLOWED: may cause irritation of the mouth and gastrointestinal tract.

IF IN EYES: may cause eye irritation.

IF ON SKIN: may cause irritation. Sensitised individuals may experience an allergic skin reaction.

IF INHALED: may cause respiratory irritation.

CHRONIC TOXICITY: Octamethylcyclotetrasiloxane is considered a suspected reproductive toxicant

#### **Supporting Data**

| Acute   | Oral<br>Dermal      | Using LD <sub>50</sub> 's for ingredients, the Acute Toxicity Estimate (ATE) (oral) for the mixture is >2,000 mg/kg. Data considered includes: Dimethylsiloxane, hydroxyl terminated 15400mg/kg (rat), titanium dioxide >20000mg/kg (rat), Methyl-O,O',O''-butan-2-on-trioximo-silane 2463 mg/kg (rat), Octamethylcyclotetrasiloxane 1540mg/kg (rat). Using LD <sub>50</sub> 's for ingredients, the Acute Toxicity Estimate (ATE) (dermal) for the mixture |
|---------|---------------------|---|
|         | Donnai              | is >2,000 mg/kg. Data considered includes: Dimethylsiloxane, hydroxyl terminated >2000mg/kg, titanium dioxide >10000mg/kg (hamster), Methyl-O,O',O''-butan-2-on-<br>trioximo-silane > 2000 mg/kg bw (rat), Octamethylcyclotetrasiloxane 1770mg/kg (rat).  |
|         | Inhaled             | Using LD <sub>50</sub> 's for ingredients, the Acute Toxicity Estimate (ATE) (inhalation) for the mixture is >5mg/L/4h. Data considered includes: Dimethylsiloxane, hydroxyl terminated 8750mg/m <sup>3</sup> /7H (rat), titanium dioxide LC <sub>50</sub> 3.43-6.82mg/l air (4h, rat), Octamethylcyclotetrasiloxane 8.67mg/l (rat), 36mg/L (4hr, rat).   |
|         | Eye                 | The mixture is considered to be an eye irritant, because some of the ingredients present are considered eye irritants in more concentrated form.  |
|         | Skin                | The mixture is not considered to be a skin irritant.  |
| Chronic | Sensitisation       | The mixture is considered to be a contact sensitizer, because at least one of the ingredients (Methyl-O,O',O''-butan-2-on-trioximo-silane) present in greater than 0.1% is known to be a contact sensitizer.  |
|         | Mutagenicity        | No ingredient present at concentrations > 0.1% is considered a mutagen.   |
|         | Carcinogenicity     | No ingredient present at concentrations > 0.1% is considered a carcinogen.  |
|         | Reproductive /      | The mixture is considered to be a suspected reproductive or developmental toxicant,   |
|         | Developmental       | because at least one of the ingredients (Octamethylcyclotetrasiloxane) present in greater than 0.1% is suspected to be a reproductive or developmental toxicant.  |
|         | Systemic            | No ingredient present at concentrations > 1% is considered a target organ toxicant.   |
|         | Aggravation of      | None known.   |
|         | existing conditions |   |

12. Ecological Data

## Summary

This mixture is not considered to be ecotoxic. In all cases prevent run-off to drains, sewers and waterways.

## Supporting Data

| Aquatic                     | Using EC <sub>50</sub> 's for ingredients, the calculated EC <sub>50</sub> for the mixture is $> 100$ mg/L. Data considered includes: Methyl-O,O',O''-butan-2-on-trioximo-silane $> 100$ mg/L. |
|-----------------------------|--|
| Bioaccumulation             | No data  |
| Degradability               | No data  |
| Soil                        | No evidence of toxicity towards soil organisms.  |
| Terrestrial vertebrate      | See acute toxicity.  |
| Terrestrial invertebrate    | No evidence of toxicity towards terrestrial invertebrates.   |
| Biocidal                    | no data  |
| Environmental effect levels | No EELs are available for this mixture or ingredients  |
|                             |  |
|                             | 40 Diseased Operations   |

#### 13. Disposal Considerations

| Restrictions    | There are no product-specific restrictions, however, local council and resource consent conditions may apply, including requirements of trade waste consents.  |
|-----------------|--|
| Disposal method | Disposal of this product must comply with the Hazardous Substances (Disposal) Notice 2017 and the requirements of the Resource Management Act for which approval should be sought from the Regional Authority. The substance must be treated and therefore rendered non-hazardous before discharge to the environment. |





## Contaminated packaging

Disposal of contaminated packaging must comply with the Hazardous Substances (Disposal) Notice 2017 clause 12. Ensure that the package is rendered incapable of containing any substance and is disposed in a manner that is consistent with the requirements of the substance it contained and the material of the package. If possible reuse or recycle packaging.

|              |    | 14. Transport Information  |    |  |
|--------------|----|--|----|--|
|              | •  | oods 2005 - NZS 5433:2007<br>nis product (not a dangerous good). |    |  |
| UN number:   | NA | Proper shipping name:  | NA |  |
| Class(es)    | NA | Packing group:   | NA |  |
| Precautions: | NA | Hazchem code:  | NA |  |
|              |    |  |    |  |

## **15. Regulatory Information**

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002670, Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2020. All ingredients appear on the New Zealand Inventory of Chemicals NZIoC.

#### **Specific Controls**

| Key workplace requirements are:     |   |
|-------------------------------------|---|
| SDS                                 | To be available within 10 minutes in workplaces storing any quantity.   |
| Inventory                           | An inventory of all hazardous substances must be prepared and maintained.   |
| Packaging                           | All hazardous substances should be appropriately packaged including substances<br>that have been decanted, transferred or manufactured for own use or have been<br>supplied |
| Labelling                           | Must comply with the Hazardous Substances (Labelling) Notice 2017.  |
| Emergency plan                      | Required if > 1000L is stored.  |
| Certified handler                   | Not required.   |
| Tracking                            | Not required.   |
| Bunding & secondary containment     | Required if > 1000L is stored.  |
| Signage                             | Not required.   |
| Location compliance certificate     | Not required.   |
| Flammable zone                      | Not required.   |
| Fire extinguisher                   | Not required.   |
| Noto: The above workplace requireme | nts apply if only this particular substance is present. The complete set of controls for a  |

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

#### **Other Legislation**

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.

## 16. Other Information

#### **Abbreviations**

| Approval Code    | Approval HSR002670, Surface Coatings and Colourants (Subsidiary Hazard) Group<br>Standard 2020 Controls, EPA. www.epa.govt.nz                    |
|------------------|--|
| CAS Number       | Unique Chemical Abstracts Service Registry Number  |
| EC <sub>50</sub> | Ecotoxic Concentration 50% – concentration in water which is fatal to 50% of a test population (e.g. daphnia, fish species)                      |
| EPA              | Environmental Protection Authority (New Zealand)   |
| GHS              | Globally Harmonised System of Classification and Labelling of Chemicals, 7 <sup>th</sup> revised edition, 2017, published by the United Nations. |
| HAZCHEM Code     | Emergency action code of numbers and letters that provide information to emergency<br>services, especially fire fighters                         |
| HSNO             | Hazardous Substances and New Organisms (Act and Regulations)   |
| IARC             | International Agency for Research on Cancer  |
| D                |  |





| LEL<br>LD <sub>50</sub><br>LC <sub>50</sub><br>NZIOC<br>MSDS (SDS)<br>STEL<br>STOT RE<br>STOT SE<br>TWA<br>UEL<br>UN Number<br>WES | Lower Explosive Limit<br>Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).<br>Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population<br>(usually rats)<br>New Zealand Inventory of Chemicals<br>Material Safety Data Sheet (or Safety Data Sheet)<br>Short Term Exposure Limit - The maximum airborne concentration of a chemical or<br>biological agent to which a worker may be exposed in any 15 minute period, provided the<br>TWA is not exceeded<br>System Target Organ Toxicity – Repeated Exposure<br>System Target Organ Toxicity – Single Exposure<br>Time Weighted Average – generally referred to WES averaged over typical work day<br>(usually 8 hours)<br>Upper Explosive Limit<br>United Nations Number<br>Workplace Exposure Standard - The airborne concentration of a biological or chemical<br>agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a<br>week). The WES relates to exposure that has been measured by personal monitoring<br>using procedures that gather air samples in the worker's breathing zone. |
|--|--|
| References   |  |
| Data<br>Controls<br>WES<br>Other References:   | Unless otherwise stated comes from the EPA HSNO chemical classification information<br>database (CCID).<br>EPA notices, www.epa.govt.nz, Health and Safety at Work (Hazardous Substances)<br>Regulations 2017, www.legislation.govt.nz<br>The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available<br>on their web site – www.worksafe.govt.nz.<br>Suppliers SDS, EU ECHA, ingredients SDS's, ChemIDplus   |
| Review   |  |
| Date<br>July 2023  | Reason for review<br>Not applicable – new SDS  |

#### Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely GHS 7 classifications for this SDS have been estimated based on general information from the supplier (e.g., hazard, toxicological). This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: +64 21 1040951

