

Screw fixing of Sump into recessed blocking

Leaf grate

Viking Enviroclad TPO waterproofing membrane 1.52 mm thick, install as per manufacturers instructions

NOTE:
1/ Overflow to match outlet capacity.
2/ Overflow to be plumbed independent of stormwater, through soffit or exterior wall

Notes:
Sumps to be plumbed with flexible hose-clamped couplings such as Dux or PlumbQwik

Overflow insert

Substrate

Viking PIR Polyiso Insulation

Viking Vapour Barrier, install as per manufacturers instructions

Viking sump / overflow IMR120T
TPO weldable, installed as per manufacturers instructions.

NOTE:
Substrate to comply with current Viking Roofspec Masterspec specification
Substrate Checklist available from www.vikingroofspec.co.nz

DRAWING TITLE

Viking WarmRoof - Enviroclad
Penetration_Sump Outlet with Overflow

NOTES:

- * Angle fillets are not required at upstands for Enviroclad
- * All fixings, cladding and structure are indicative only unless noted
- * All details to be read in conjunction with Viking Specifications

WarmRoof System is Branz Appraised - 713

DRAWING

INFORMATION ONLY

Scale:	Date:	Drawn:	Viking
Not to Scale	01/03/2022		
Detail Ref:			

VIK_WRE_003_PENESUMP

Roofspec
Viking
Taking care of detail