

1. Identification of Substance & Company

Product

Product name Prime-Tek Epoxy Primer A

Product code not assigned **HSNO** approval HSR002679

Approval description Surface Coatings and Colourants (Carcinogenic) Group Standard 2020

UN number 3082 **DG class**

Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, contains

Bisphenol A

Packaging group Ш Hazchem code 37

Epoxy primer part A

Company Details

Company Viking Roofspec

Physical Address 80 Alexander Crescent PO Box 14 451 Otara Panmure

Auckland Auckland 1741 New Zealand New Zealand

Telephone 0800 729 799 0800 729 788 Fax

Website www.vikingroofspec.co.nz

Emergency Telephone Number: 0800 764 766

2. Hazard Identification

Approval

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO, Approval HSR002679, Surface Coatings and Colourants (Carcinogenic) Group Standard 2020). The substance has been classified as hazardous according to the criteria in the Hazardous substances (Hazard Classification) Notice 2020.

GHS 7 Classes

Hazard Statements

Eye irritant category 2

Respiratory sensitiser category 1

Skin sensitiser category 1

Mutagen category 1 Carcinogen category 1

Reproductive toxicity category 1 STOT* repeated exposure category 2

Chronic aquatic category 2 **SYMBOLS**

H319 - Causes serious eye irritation. H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317 - May cause an allergic skin reaction.

H340 - May cause genetic defects.

H350 - May cause cancer.

H360 - May damage fertility or the unborn child.

H373 - May cause damage to organs through prolonged or repeated exposure.

H411 - Toxic to aquatic life with long lasting effects.

ANGER



Hazard Statements

There are no other classifications that are known to apply.

Precautionary Statements

Prevention P103 - Read label before use.

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe vapours.



P264 - Wash hands thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product P272 - Contaminated work clothing should not

be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection.

P285 - In case of inadequate ventilation wear respiratory protection.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, Response

if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P304+P341 - IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position

comfortable for breathing.

P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

P302+P352 - IF ON SKIN: Wash with plenty of soap and water.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P363 - Wash contaminated clothing before reuse.

P308+P313 - IF exposed or concerned: Get medical advice/ attention.

Storage P405 - Store locked up.

Disposal P501 - Dispose of contents/container in accordance with local/regional/national/international regulation.

3. Composition / Information on Ingredients

Component	CAS/ Identification	Conc (%)
Limestone	1317-65-3	50-60%
Bisphenol A diglycidyl ether resin	25068-38-6	40-50%
titanium dioxide	13463-67-7	1-5%
Oxirane	75-21-8	0.1-1%
1,4-dioxane	123-91-1	0.1-1%
acetaldehyde	75-07-0	0.1-1%

This is a commercial product whose exact ratio of components may vary. Trace quantities of impurities are also likely.

4. First Aid

General Information

If medical advice is needed, have product container or label at hand. You should call the National Poisons Centre if you feel that you may have been harmed or irritated by this product. The number is 0800 764 766 (0800 POISON) (24 hr emergency service).

Recommended first aid

Ready access to running water is required. Accessible eyewash is required.

facilities

Exposure Swallowed

IF SWALLOWED: Call a POISON CENTRE or doctor/physician if you feel unwell. Rinse

mouth. Do NOT induce vomiting. Give a glass of water to drink.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Skin contact IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Inhaled IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position

comfortable for breathing. If experiencing respiratory symptoms: Call a POISON

CENTRE or doctor/physician.

Advice to Doctor

Treat symptomatically

5. Firefighting Measures

Fire and explosion hazards: Suitable extinguishing substances:

Unsuitable extinguishing

substances:

There are no specific risks for fire/explosion for this chemical. It is non-flammable. Carbon dioxide, extinguishing powder or water jet. Fight larger fires with water jet or alcohol resistant foam.

Unknown.

Page 2 of 7 July 2023

Product Name: Prime-Tek Epoxy Primer A





Products of combustion: Carbon dioxide, and if combustion is incomplete, carbon monoxide and smoke. Water.

May form toxic mixtures in air and may accumulate in sumps, pits and other low-lying

spaces, forming potentially explosive mixtures.

Protective equipment: Self-contained breathing apparatus. Safety boots, non-flammable overalls, gloves, hat

and eye protection.

Hazchem code: NA

6. Accidental Release Measures

Containment If greater than 1000L is stored, secondary containment and emergency plans to manage

any potential spills must be in place. In all cases design storage to prevent discharge to

storm water.

Emergency procedures In the event of spillage alert the fire brigade to location and give brief description of

hazard. Stop the source of the leak, if safe to do so. Shut off all possible sources of ignition. Wear protective equipment to prevent skin, eye and respiratory exposure. Clear area of any unprotected personnel. Contain using sand, earth or vermiculite. Do not use sawdust. Prevent by whatever means possible any spillage from entering drains, sewers,

or water courses. (If this occurs contact your regional council immediately).

clean-up of spills, as they may create fire or environmental hazard. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or

waterways has occurred advise local emergency services.

Disposal Mop up and collect recoverable material into labelled containers for recycling or salvage.

Recycle containers wherever possible. This material may be suitable for approved

landfill. Dispose of only in accord with all regulations.

Wear protective equipment to prevent skin and eye contamination and the inhalation of

vapours. Work up wind or increase ventilation.

7. Storage & Handling

Storage Avoid storage of harmful substances with food. Store out of reach of children.

Containers should be kept closed in order to minimise contamination. Keep from extreme heat and open flames. Avoid contact with incompatible substances as listed in

Section 10

Handling Keep exposure to a minimum, and minimise the quantities kept in work areas. See

section 8 with regard to personal protective equipment requirements. Avoid skin and eye

contact and inhalation of vapour, mist or aerosols.

8. Exposure Controls / Personal Protective Equipment

Workplace Exposure Standards

Precautions

A workplace exposure standard (WES) has not been established by WorkSafe NZ for this product. There is a general limit of 3mg/m³ for respirable particulates and 10mg/m³ for inhalable particulates when limits have not otherwise been established.

NZ Workplace Ingredient WES-TWA WES-STEL

Exposure Stds limestone 10mg/m³ - titanium dioxide 10mg/m³ -

Oxirane 0.1ppm, 0.2mg/m³ (carc 1, skin, dsen, rsen) - 1,4-dioxane 5ppm, 18mg/m³ carc 1, skin -

acetaldehyde no TWA, ceiling: 20ppm. 36mg/m³ (carc 2)

Engineering Controls

In industrial situations, it is expected that employee exposure to hazardous substances will be controlled to a level as far below the WES as practicable by applying the hierarchy of control required by the Health and Safety at Work Act (2015) and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016. Exposure can be reduced by process modification, use of local exhaust ventilation, capturing substances at the source, or other methods. If you believe air borne concentrations of mists, dusts or vapours are high, you are advised to modify processes or increase ventilation.

Personal Protective Equipment

General Personal Protective Equipment (PPE) should not be used as the primary means of

exposure protection, except in the event of an accident or emergency situation or where

all other means of protection have proven to inadequate.

Clean PPE after use or dispose of as appropriate. Store PPE for re-use in a clean place. Regular training on the correct use of PPE should be provided. In particular the correct fitting and use of respirators and where applicable the cleaning of respirators should be undertaken.

Page 3 of 7 July 2023

Product Name: Prime-Tek Epoxy Primer A



Eyes



Avoid contact with eyes. Use safety glasses and or chemical splash goggles if splashes are possible. Select eye protection in accordance with AS/NZS 1337.

Skin



Avoid repeated or prolonged skin contact. Wear overalls, rubber boots and impervious gloves. Nitrile gloves are recommended. Protective gloves or suitably resistant material must comply with AS 2161. Replace frequently. Gloves should be checked for tears or holes before use. Protective clothing must comply with AS 2919, AS3765.1 or AS3765.2. PVC or rubber boots must comply with AS/NZS 2210.2 and selected and maintained in accordance with AS/NS2210.1. Remove protective clothing and wash exposed areas with soap and water prior to eating, drinking or smoking. Wash hands after handling. A respirator when airborne concentrations approach the WES (section 8). Respirators must have filters appropriate to the duty and comply with AS/NZS1716 and selected, used and maintained in accordance with AS/NS 1715. Use a respirator with an organic vapour cartridge and a particulate filter. If using a respirator, ensure that the cartridges are correct for the potential air contamination and are in good working order. Fit testing and clear guidelines and training for use and maintenance of PPE are necessary.

Respiratory



WES Additional Information

Not applicable

9. Physical & Chemical Properties

Appearance white liquid Odour faint aromatic **Odour Threshold** no data pН no data Freezing/melting point no data not specified **Boiling Point Flashpoint** >100°C

not classed as flammable **Flammability**

Upper & lower flammable limits no LEL or UEL Vapour pressure no data Vapour density no data Specific gravity/density 1.41g/cm³ Solubility not specified Partition coefficient no data **Auto-ignition temperature** no data **Decomposition temperature** no data **Viscosity** no data

Particle Characteristics no data

10. Stability & Reactivity

Stability Stable

Conditions to be avoided Containers should be kept closed in order to avoid contamination. Keep from extreme

heat and open flames.

Oxide of carbon, hydrocarbons.

Incompatible groups Isocyanates and strong oxidising agents.

Substance Specific none known

Incompatibility

Hazardous decomposition

products

Hazardous reactions none known

11. Toxicological Information

Summary

IF SWALLOWED: may cause gastrointestinal irritation. Consult a doctor.

IF IN EYES: may cause irritation.

IF ON SKIN: sensitised individuals may experience an allergic skin reaction.

IF INHALED: sensitised individual may experience an allergic reaction, e.g. asthma.

CHRONIC TOXICITY: Oxirane, 1,4-dioxane and acetaldehyde are considered carcinogens. Oxirane is considered a mutagen. Acetaldehyde is considered a reproductive toxicant.

Page 4 of 7

July 2023 Product Name: Prime-Tek Epoxy Primer A



Inhaled

Supporting Data

Acute Oral Using LD₅₀'s for ingredients, the Acute Toxicity Estimate (ATE) (oral) for the mixture is

>2,000 mg/kg. Data considered includes: limestone >5000mg/kg, Bisphenol A diglycidyl ether resin 15600mg/kg (mouse), 10.7mL/kg (rat), titanium dioxide >20000mg/kg (rat), Oxirane 72mg/kg bw (rat), 1,4-dioxane 2000mg/kg (cat), acetaldehyde 661 mg/kg (rat). Using LD $_{50}$'s for ingredients, the Acute Toxicity Estimate (ATE) (dermal) for the mixture

Dermal Using LD $_{50}$'s for ingredients, the Acute Toxicity Estimate (ATE) (dermal) for the mixture is >2,000 mg/kg. Data considered includes: limestone NA, Bisphenol A diglycidyl ether

resin >20mL/kg (rabbit), titanium dioxide >10000mg/kg (hamster), Oxirane no data, 1,4-

dioxane 7600mg/kg bw (rabbit), acetaldehyde data unavailable, 0 0, 0 0, 0 0 Using LD₅₀'s for ingredients, the Acute Toxicity Estimate (ATE) (inhalation) for the

mixture is >5mg/L/4h. Data considered includes: limestone NA, Bisphenol A diglycidyl ether resin not reported, titanium dioxide LC₅₀ 3.43-6.82mg/l air (4h, rat), practically non toxic, Oxirane 800ppm (rat), 1,4-dioxane 37g/m³ (2h), acetaldehyde data unavailable, 0

0, 0 0, 0 0

Eye The mixture is considered to be an eye irritant, because some of the ingredients present

are considered eye irritants in more concentrated form.

Skin The mixture is not considered to be a skin irritant.

Chronic Sensitisation The mixture is considered to be a contact and respiratory sensitizer, because at least one

of the ingredients present in greater than 0.1% is known to be a contact and respiratory

sensitizer.

Mutagenicity The mixture is considered to be a known or presumed mutagen, because at least one of

the ingredients present in greater than 0.1% is known or presumed to be a mutagen.

The mixture is considered to be a known or presumed carcinogen, because at least one of the ingredients present in greater than 0.1% is known or presumed to be a carcinogen.

Reproductive / The mixture is considered to be a known or presumed reproductive or developmental toxicant, because at least one of the ingredients present in greater than 0.1% is known or

presumed to be a reproductive or developmental toxicant.

Systemic The mixture is considered to be a suspected target organ toxicant, because at least one

of the ingredients present in greater than 1% is suspected to be a target organ toxicant.

Aggravation of None known.

existing conditions

12. Ecological Data

Summary

This mixture is considered toxic towards aquatic organisms with long lasting effects. In all cases prevent run-off to drains, sewers and waterways.

Supporting Data

Aquatic Using EC₅₀'s for ingredients, the calculated EC₅₀ for the mixture is > 100 mg/L. Data

considered includes: Bisphenol A diglycidyl ether resin 1.2 mg/L (96h, Oncorhynchus

mykiss), 2.7 mg/L (48h, Daphnia magna).

Bioaccumulation No data
Degradability No data

Soil EPA has not classified the mixture as ecotoxic in the soil environment. The soil toxicity

value for the mixture is \geq 100 mg/kg.

Terrestrial vertebrate See acute toxicity.

Terrestrial invertebrateNo evidence of toxicity towards terrestrial invertebrates.

Biocidal no data

Environmental effect levels No EELs are available for this mixture or ingredients

13. Disposal Considerations

Restrictions There are no product-specific restrictions, however, local council and resource consent

conditions may apply, including requirements of trade waste consents.

Disposal methodDisposal of this product must comply with the Hazardous Substances (Disposal) Notice 2017 and the requirements of the Resource Management Act for which approval should

be sought from the Regional Authority. The substance must be treated and therefore

rendered non-hazardous before discharge to the environment.

Contaminated packaging

Disposal of contaminated packaging must comply with the Hazardous Substances

(Disposal) Nation 2017 along the table packaging is produced in a packaging in the table packaging is produced in a packaging in the table packaging is produced in a packaging in the table packaging is produced in a packaging in the table packaging in table packa

(Disposal) Notice 2017 clause 12. Ensure that the package is rendered incapable of containing any substance and is disposed in a manner that is consistent with the requirements of the substance it contained and the material of the package. If possible

reuse or recycle packaging.

Roofspec

Taking care of detail

Prime-Tek Epoxy Primer A **Safety Data Sheet**

14. Transport Information

Land Transport Rule: Dangerous Goods 2005 - NZS 5433:2007

Transport according to NZS 5433 (Transport of Hazardous Substances on Land). Considered a dangerous good for transport.

ENVIRONMENTALLY HAZARDOUS UN number: 3082 Proper shipping name:

SUBSTANCE, LIQUID (contains

bisphenol A)

Ш

9 Class(es) Packing group: **Precautions:**

Marine Pollutant Hazchem code: 3Z

IMDG

UN number: 3082 Proper shipping name: **ENVIRONMENTALLY HAZARDOUS**

SUBSTANCE, LIQUID (contains

bisphenol A)

Class(es) Packing group:

Precautions: Marine Pollutant F-A, S-F **EmS**

IATA

3082 **ENVIRONMENTALLY HAZARDOUS UN number:** Proper shipping name:

SUBSTANCE, LIQUID (contains

Product Name: Prime-Tek Epoxy Primer A

bisphenol A)

Class(es) Packing group: Ш

Precautions: Marine Pollutant

15. Regulatory Information

This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002679, Surface Coatings and Colourants (Carcinogenic) Group Standard 2020. All ingredients appear on the New Zealand Inventory of Chemicals NZIoC.

Specific Controls

Key workplace requirements are:

SDS To be available within 10 minutes in workplaces storing any quantity.

An inventory of all hazardous substances must be prepared and maintained. Inventory

Packaging All hazardous substances should be appropriately packaged including substances that

manufactured for own use or have been supplied

Must comply with the Hazardous Substances (Labelling) Notice 2017. Labelling

Emergency plan Required if > 1000L is stored.

Certified handler Not required. Tracking Not required.

Bunding & secondary containment Required if > 1000L is stored. Signage Required if > 1000L is stored.

Location compliance certificate Not required. Flammable zone Not required. Fire extinguisher Not required.

Note: The above workplace requirements apply if only this particular substance is present. The complete set of controls for a location will depend on the classification and total quantities of other substances present in that location.

Other Legislation

In New Zealand, the use of this product may come under the Resource Management Act and Regulations, the Health and Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016, local Council Rules and Regional Council Plans.



16. Other Information

Abbreviations

Approval Code

Approval HSR002679, Surface Coatings and Colourants (Carcinogenic) Group Standard

2020 Controls, EPA. www.epa.govt.nz

CAS Number Unique Chemical Abstracts Service Registry Number

ECotoxic Concentration 50% − concentration in water which is fatal to 50% of a test

population (e.g. daphnia, fish species)

EPA Environmental Protection Authority (New Zealand)

GHS Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised

edition, 2017, published by the United Nations.

HAZCHEM Code Emergency action code of numbers and letters that provide information to emergency

services, especially fire fighters

HSNO Hazardous Substances and New Organisms (Act and Regulations)

International Agency for Research on Cancer

LEL Lower Explosive Limit

LD₅₀ Lethal Dose 50% – dose which is fatal to 50% of a test population (usually rats).

Lethal Concentration 50% – concentration in air which is fatal to 50% of a test population

(usually rats)

NZIoC New Zealand Inventory of Chemicals

MSDS (SDS)

Material Safety Data Sheet (or Safety Data Sheet)

STEL Short Term Exposure Limit - The maximum airborne concentration of a chemical or

biological agent to which a worker may be exposed in any 15 minute period, provided the

TWA is not exceeded

STOT RESystem Target Organ Toxicity – Repeated Exposure **STOT SE**System Target Organ Toxicity – Single Exposure

TWA Time Weighted Average – generally referred to WES averaged over typical work day

(usually 8 hours)

UEL Upper Explosive Limit
UN Number United Nations Number

WES Workplace Exposure Standard - The airborne concentration of a biological or chemical

agent to which a worker may be exposed during work hours (usually 8 hours, 5 days a week). The WES relates to exposure that has been measured by personal monitoring

using procedures that gather air samples in the worker's breathing zone.

References

Data

Unless otherwise stated comes from the EPA HSNO chemical classification information

database (CCID).

Controls EPA notices, www.epa.govt.nz, Health and Safety at Work (Hazardous Substances)

Regulations 2017, www.legislation.govt.nz

WES The latest NZ Workplace Exposure Standards, published by WorkSafe NZ and available

on their web site – www.worksafe.govt.nz.

Other References: Suppliers SDS, EU ECHA, ingredients SDS's, ChemIDplus

Review

DateReason for reviewJuly 2023Not applicable – new SDS

Disclaimer

This SDS was prepared by Datachem LTD and is based on our current state of knowledge, including information obtained from suppliers. The SDS is given in good faith and constitutes a guideline (not a guarantee of safety). The level of risk each substance poses is relevant to its properties (as summarised in the SDS) AND HOW THE SUBSTANCE IS USED. While guidelines are given for personal protective equipment, such precautions must be relevant to the use. The likely GHS 7 classifications for this SDS have been estimated based on general information from the supplier (e.g., hazard, toxicological). This SDS is copyright Datachem and must not be copied, edited or used for other than intended purpose. To contact the SDS author, email info@datachem.co.nz or phone: +64 21 1040951.

